

Panelmonteret stik kontakt

Varenr. 1383




- lige

Tekniske data

| | |
|----------------------------|---------------------|
| Ampere | 16 A |
| Poler | 5 p |
| Volt | 400 V |
| Klokposition | 6 h |
| Hertz | 50-60 Hz |
| Forbindelsesteknologi | Skruekontakt |
| Kontakt | standard |
| Beskyttelsestype | IP44 |
| Flange | 72x65 mm |
| Fikseringshul | 52x52 mm |
| Vægt | 180 g |
| Overensstemmelseserklæring | VDE, EAC, Kema, CQC |

Dimensioner



| Drawing 1 MB 259 | Amp. Poles | 16 | | |
|--|---------------|-----------|-----------|-----------|
| | | 3 | 4 | 5 |
| Dim. in mm | a | 62 | 72 | 72 |
| | b | 62 | 65 | 65 |
| | c | 54 | 54 | 54 |
| | d | 47 | 52 | 52 |
| | e | 47 | 52 | 52 |
| | f | 5,5 | 5,5 | 5,5 |
| | g | 8 | 8 | 8 |
| | g1 | 2 | 2 | 2 |
| | h | 68 | 77 | 85 |
| | h1 | 7 | 7 | 11 |
| | k | 32 | 32 | 32 |
| | l | 50 | 52 | 57 |
| Terminal for cond. cross section (mm ²) min.-max. | | 1,5 —4 | 1,5 —4 | 1,5 —4 |