

Panelmonteret stik kontakt

Varenr. 209AB




- skrueterminaler
- **X-CONTACT®**
- 20° hældning
- pilotkontakt

Tekniske data

Ampere	63 A
Poler	5 p
Volt	400 V
Klokposition	6 h
Hertz	50-60 Hz
Forbindelsesteknologi	Skruekontakt
Kontakt	X-CONTACT®
Beskyttelsestype	[ClassificationAttributeValueModel (8796126741088@43), ClassificationAttributeValueModel (8796126741088@43)]
Lukker	false
Flange	110x106 mm
Fikseringshul	85x77 mm
Inklination	20 °
Vægt	670 g

Dimensioner



1 MB 298 1 MB 601	Amp. Poles	63			125		
		3	4	5	3	4	5
Dim. in mm							
a		110	110	110	114	114	114
b		106	106	106	110	110	110
c		85	85	85	75	75	75
d		85	85	85	90	90	90
e		77	77	77	90	90	90
f		6.2	6.2	6.2	6.2	6.2	6.2
g		12	12	12	13	13	13
g1		2	2	2	2	2	2
h		128	128	128	133	133	133
i		113	113	113	126	126	126
k		67	67	67	103	103	103
l		92	92	92	94	94	94
l1		98	98	98	107	107	107
<		20°	20°	20°	15°	15°	15°
Terminal for cond. cross section (mm²) min.-max.		6	6	6	25	25	25
		-25	-25	-25	70	70	70