

AMAXX® Stikkombinationer

Varenr. 950013




- præforbundet til installation
- kabinet hængslet på siden
- kabinet og indsættelse af **AMAPLAST**
- sikring bag et gennemsigtigt dæksel

Tekniske data

CEE 63 A, 5 p, 400 V	1
CEE 32 A, 5 p, 400 V	1
CEE 16 A, 5 p, 400 V	1
SCHUKO®	4
Fusing	<ul style="list-style-type: none"> • 1 RCD 63 A, 4 p, 0,03 A • 1 MCB 32 A, 3 p, C • 1 MCB 16 A, 3 p, C • 4 MCB 16 A, 1 p, C
Præ-sikring maks.	63 A
InA	63 A
RDF	0.65
Connection / feeder cable	<ul style="list-style-type: none"> • til 2 kabler op til 5 x 25 mm²
Beskyttelsestype	IP44
Lukker	false
Kabinetmateriale	Plast
Vægt	9960 g
Højde	650 mm
Bredde	225 mm
Overensstemmelseserklæring	EAC

Dimensioner



Drawing 1 MB 540

Depth dimensions at various fittings.

Receptacles	Degrees	Depth
SCHUKO® 16A, 230 V	IP 44	186 mm
	IP 67	208 mm
CEE 16A, 3p, 230V	IP 44	216 mm
	IP 67	220 mm
CEE 16A, 5p, 400V	IP 44	222 mm
	IP 67	226 mm
CEE 32A, 5p, 400V	IP 44	231 mm
	IP 67	236 mm
CEE 63A, 5p, 400V	IP 44	260 mm
	IP 67	260 mm

Cable entries: closed for cut out. 2 x M 40 each on top and bottom, 2 x M 20 each on top and bottom for cut out.